

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01 KT81EE Double Sided Tissue Tape



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

Carrier			
Description		Grade	
Shelf Life		12 months stored in ambient temperature	
Shelf Life Solid Rubbers		3-6 months	
Non-woven tissue		12 g/m ²	
Release Liner			
Grade	Colour	Weight	
Glassine	Amber	80 g/m ²	
Adhesive			
Type	Grade	Thickness	
Waterbased acrylic	Modified	80 micron	
Perfomance			
Peel adhesion to steel	Loop tack	Release from liner	Temperature range
800 N/m	600 N/m	10 N/m	-20°C to 120°C
Change Control Date		Change	
03/09/2013		Created	



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

